



LAMP WOOL PAD

Application and Specifications

HEAVY CUT POLISHING PAD

Application

- Ensure that the polishing pad is used according to the sanding level of polishing compound in use.
- Only work on cool surfaces.
- Wash your vehicle with Nasiol® Cleanion Pro and use clay bar and/or iron decontaminer with regard to the condition of paintwork, prior to polishing.
- Prepare the surface by applying Nasiol® Clean to remove any dust or residual contamination.
- Mask all exceptional parts may come into contact with the polisher by using a masking tape to avoid potential damages.
- Use Nasiol® Velcro Backing Plate to attach any polishing pad to the polisher.
- Remove scratches, oxidation mark or haze from the paintwork by using Nasiol® CleaRub polishing compounds at different cutting levels, according to the type of imperfections.
- Always work with care on the paintwork and pay attention to remove imperfections in minimal decrease of the clearcoat thickness.
- Keep the treated surface away from direct sunlight, water and other contamination during the polishing.

Specifications

Packaging	1x Foam Pad (65 ±2 g)
Pad Dimensions	15 x15 cm
Thickness	2.5 cm
Color	Dark Red/Burgundy
Recommended Speed	1400-2000 rpm
Washing Machine Compatibility	Yes
Material	Polyurethane